

MATERIAL SAFETY DATA SHEET

XP LAB, INC.
946 W. HAWTHORN ST.
SAN DIEGO, CA 92101
Phone (619)233-3111 Fax (619)233-3112

Xp3D-MG

Page: 1
Date: January, 2015
MSDS: XPM/2111-5

SECTION 1: PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

SECTION 1: PRODUCT NAME: Xp3D-MG

EMERGENCY TELEPHONE NUMBERS: XP Lab, Inc. (619)233-3111
Chemtrec USA (800)424-9300
Intl. (703)527-3887

SECTION 2: HAZARDOUS INFORMATION

NON REGULATED

SECTION 3: HEALTH INFORMATION AND PROTECTION

POTENTIAL HEALTH EFFECTS

EYE:

May cause moderate eye irritation which may be slow to heal. Vapors may irritate eyes. May cause moderate corneal injury.

SKIN:

Low order of toxicity. Prolong or repeated exposure may cause skin irritation. A single prolong exposure may result in the material being absorbed in harmful amounts. Excessive exposure may cause hemolysis. Repeated minor exposure may result in absorption of harmful amounts.

INGESTION:

Minimal toxicity. Single dose oral toxicity is considered to be moderate. Small amounts swallowed incidental are not likely to cause injury. Swallowing larger amounts may cause injury.

INHALATION:

A single prolonged excessive inhalation exposure may cause adverse effect. Excessive exposure may cause irritation in the upper respiratory tract.

TERATOLOGY (BIRTH DEFECTS):

Birth defects are unlikely. Exposures having no effect in the mother should have no effect on the fetus. Did not cause birth defects in animals.

SECTION 4: FIRST AID

EYE CONTACT

Irrigate with flowing water immediately and continuously for 15 minutes. If irritation persist, get medical attention.

SKIN CONTACT:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated cloths and shoes. Call physician if irritation continues.

INGESTION:

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Consult medical personnel.

INHALATION:

Remove the affected victim from exposure. Remove to fresh air if effect occur. Consult a physician.

SECTION 5: FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

| | |
|---------------------------|------|
| Flash Point: | NONE |
| Method Used: | PMCC |
| Autoignition Temperature: | NONE |

FLAMMABILITY LIMITS

| | |
|------|-----|
| LFL: | N/A |
| UFL: | N/A |

HAZARDOUS COMBUSTION PRODUCTS:

During a *fire*, smoke may contain the original material in addition to toxic and/or irritating compounds.

Violent steam generation or eruption may occur on application of direct water stream to hot liquids. Vapor are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flashback may occur.

EXTINGUISHING MEDIA:

Water fog or fine spray. Carbon Dioxide. Dry chemical. Foam. Alcohol resistant foam (ATC type) are preferred if available. General purpose synthetic foams (including AFFF) or protein foams may function, but much less effectively.

DO NOT use direct water stream.

SECTION 6: SPILL CONTROL PROCEDURE

Eliminate all sources of ignition in vicinity of spill or release vapor to avoid fire or explosion. For large spill, warn public of downwind explosion hazard. Check area with explosion meter before reentering area. Ground and bond all containers and handling equipment. Prevent liquid from entering sewers. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust. Recover by pumping (use an explosion proof or hand pump) or with an expert absorbent.

SECTION 7: HANDLING AND STORAGE

HANDLING:

Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. No smoking, open flames or sources of ignition in handling and storage area. Never use air pressure for transferring product. Electrically ground all equipment.

STORAGE:

Keep containers tightly close when not in use. Store in carbon steel, stainless steel, Teflon containers.

SECTION 8: PERSONAL PROTECTION

EYE AND FACE PROTECTION:

Use chemical goggles. If vapor exposure causes eye discomfort, use a full-face respirator.

SKIN PROTECTION:

Use protective clothing impervious to this material.

RESPIRATORY PROTECTION:

Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required, use an approved air-purifying or positive pressure supplied-air respirator depending in the potential airborne concentration.

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable under recommended storage conditions.
CONDITION TO AVOID: Avoid static discharge.
HAZARDOUS DECOMPOSITION PRODUCTS: Does not normally decompose.
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

ECOTOXISITY
Material is non-toxic

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE:
N/A
BIODEGRADATION & PERSISTENCE
N/A

SECTION 13: DISPOSAL CONSIDERATION

May be disposed of in a secured sanitary landfill.

SECTION 14: TRANSPORT REGULATION

DEPARTMENT OF TRANSPORTATION: NOT REGULATED
PROPER SHIPPING NAME: Magnesium concentration

SECTION 15: REGULATORY INFORMATION

Reportable Quantity: N/A
NFPA RATING: HEALTH 1
FLAMMABILITY 0
REACTIVITY 0

SECTION 16: OTHER INFORMATION

TOXIC SUBSTANCE CONTROL ACT (TSCA):

All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

OSHA HAZARD COMMUNICATION STANDARD:

This product is a Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

NOTICE: The information presented in good faith and believed to be accurate as of the effective date shown above. However no warranty express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that their activities comply with federal, state or provincial, and local laws.